

Capítulo 8, página 322, Tabela 8.3:

Tabela 1 Exemplo de funcionamento do algoritmo Shift-And-Aproximado, permitindo um erro de inserção ($R'_0 = (R_0 \gg 1)|10^{m-1} \& M[T[i]]$ e $R'_1 = (R_1 \gg 1) \& M[T[i]]|R_0|10^{m-1}$)

Texto	$(R_0 \gg 1) 10^{m-1}$	R'_0	$R_1 \gg 1$	R'_1
o	1 0 0 0 0	0 0 0 0 0	0 1 0 0 0	1 0 0 0 0
s	1 0 0 0 0	0 0 0 0 0	0 1 0 0 0	1 0 0 0 0
t	1 0 0 0 0	0 0 0 0 0	0 1 0 0 0	1 0 0 0 0
e	1 1 0 0 0	0 1 0 0 0	0 1 0 0 0	1 1 0 0 0
s	1 0 1 0 0	0 0 1 0 0	0 1 1 0 0	1 1 1 0 0
t	1 0 0 1 0	1 0 0 1 0	0 1 1 1 0	1 0 1 1 0
e	1 1 0 0 1	0 1 0 0 1	0 1 0 1 1	1 1 0 1 1
s	1 0 1 0 0	0 0 1 0 0	0 1 1 0 1	1 1 1 0 1
t	1 0 0 0 0	0 0 0 0 0	0 1 1 1 0	1 0 1 0 0
e	1 0 0 0 0	1 0 0 0 0	0 1 0 1 0	1 0 0 1 0
s	1 1 0 0 0	0 1 0 0 0	0 1 0 0 1	1 1 0 0 1
s	1 0 1 0 0	0 0 1 0 0	0 1 1 0 0	1 1 1 0 0
t	1 0 0 1 0	1 0 0 1 0	0 1 1 1 0	1 0 1 1 0
a	1 1 0 0 1	0 0 0 0 0	0 1 0 1 1	1 0 0 1 0
m	1 0 0 0 0	0 0 0 0 0	0 1 0 0 1	1 0 0 0 0

Tabela 2 Exemplo de funcionamento do algoritmo Shift-And-Aproximado, permitindo um erro de inserção $R'_0 = (R_0 \gg 1)|10^{m-1} \& M[T[i]]$ e $R'_1 = (R_1 \gg 1) \& M[T[i]]|R_0|(10^{m-1})$

Texto	$(R_0 \gg 1) 10^{m-1}$	R'_0	$R_1 \gg 1$	R'_1
o	1 0 0 0 0	0 0 0 0 0	0 1 0 0 0	1 0 0 0 0
s	1 0 0 0 0	0 0 0 0 0	0 1 0 0 0	1 0 0 0 0
t	1 0 0 0 0	0 0 0 0 0	0 1 0 0 0	1 0 0 0 0
e	1 1 0 0 0	0 1 0 0 0	0 1 0 0 0	1 1 0 0 0
s	1 0 1 0 0	0 0 1 0 0	0 1 1 0 0	1 1 1 0 0
t	1 0 0 1 0	1 0 0 1 0	0 1 1 1 0	1 0 1 1 0
e	1 1 0 0 1	0 1 0 0 1	0 1 0 1 1	1 1 0 1 1
s	1 0 1 0 0	0 0 1 0 0	0 1 1 0 1	1 1 1 0 1
t	1 0 0 0 0	0 0 0 0 0	0 1 1 1 0	1 0 1 0 0
e	1 0 0 0 0	1 0 0 0 0	0 1 0 1 0	1 0 0 1 0
s	1 1 0 0 0	0 1 0 0 0	0 1 0 0 1	1 1 0 0 1
s	1 0 1 0 0	0 0 1 0 0	0 1 1 0 0	1 1 1 0 0
t	1 0 0 1 0	1 0 0 1 0	0 1 1 1 0	1 0 1 1 0
a	1 1 0 0 1	0 0 0 0 0	0 1 0 1 1	1 0 0 1 0
m	1 0 0 0 0	0 0 0 0 0	0 1 0 0 1	1 0 0 0 0